

NOTES:-

- 1. BEDDING ZONE BEDDING SAND SHALL EXTEND OVER THE FULL WIDTH OF THE TRENCH AND SHALL BE COMPACTED AT OPTIMUM MOISTURE CONTENT, TO ACHEIVE A MINIMUM COMPACTION OF 95% MMDD.
 - BY TAMPERING, ROLLING AND/OR VIBRATING TO A MIN. COMPACTION OF 95% MMDD. SAND SHALL
- 2. BACKFILL ZONES BE PLACED IN LAYERS NOT EXCEEDING 150mm COMPACTED THICKNESS (200mm UNCOMPACTED). MATERIAL SHALL BE PLACED IN LAYERS NOT EXCEEDING 150mm COMPACTED THICKNESS
- (200mm UNCOMPACTED), LAYERS SHALL BE COMPACTED BY CONVENTIONAL MECHANICAL METHODS, 3. SERVICE TRENCHES THROUGH NATURAL, AND LANDSCAPED AREAS, SHALL BE REINSTATED WITH CLEAN FILL ABOVE THE BACKFILL ZONE 1, TO MATCH THE EXISTING SURFACE.
- 4. EXCAVATED MATERIAL ALL EXCAVATED MATERIAL SHALL BE REMOVED FROM THE SITE. EXCAVATED MATERIAL SHALL NOT BE REUSED IN THE TRENCH BACKFILL.

STANDARD DETAIL

BACKFILLING OF TRENCHES SMALL DIAMETER CONDUITS LESS THAN 250mm

DRAWN / DESIGNED PREVIOUS ISSUE DATE COPY ISSUE DATE ISSUED DATE July 2002 January 2007 J.R.



DRAWING NO.

SHEET

14 R

Д4